

# H-POWER

Hydraulic modernization



# Performance. Efficiency. Reliability.

Aging hydraulic elevator systems can become less reliable and performance can deteriorate. This means increased maintenance requirements, shutdowns, service calls and safety concerns.

With more than 30 performance-optimizing features in our H-Power modernization package, we replace your hydraulic elevator's most critical components. You'll feel and see the difference the first time you step into your elevator.

# H-Power performance package overview:

### 1 TAC series controller

Our digital controller offers increased reliability, reduced wiring and optimized efficiency through its 32-bit microprocessor. It also includes:

- Battery lowering unit
   Prevents entrapments and provides supplemental power to the controller in a power outage. It also eliminates the need for a costly power generator.
- Solid state starter
   Minimizes power surges and provides smooth, quiet and reliable motor operation.
- Elevator positioning encoder Communicates the elevator's location. This helps promote a safe and level landing for passengers when boarding and exiting.
- Nonproprietary user-interface tool
   Provides unrestricted access for on-board adjusting and troubleshooting, keeping troubleshooting calls short.
- MAX

Provides real-time, cloud-based predictive maintenance, which increases your elevator's uptime.

### 2 Power unit (optional)

This key component reduces noise and vibration during operation — allowing for a quiet and smooth ride. The compact design uses less materials to construct and takes up less space. Furthermore, precise operation of the unit increases leveling accuracy and improves passenger safety.

### 3 Universal door operator

Faulty doors are the elevator industry's most frequent service call. This new technology improves door reliability and provides quick and smooth door operation.

### 4 MOD Fusion fixtures

Our stainless steel fixture line includes car operating panels, hall fixtures and car riding lanterns that improve elevator appearance and functionality. Fixtures are also easy to install, do not damage the walls and are in full compliance with U.S. and Canadian fire service codes.

### 5 Wiring package

Our cable and hoistway wiring system communicates with multiple devices through a single wire using advanced CAN-BUS technology. It helps provides afer and more efficient elevator operations and maintenance.

H-Power technical specifications	
Openings	Front and rear (selective)
Stops	Up to 8
Power	200-208V, 220-240V,
supply	460-480V, 575-600V,
	50/60 Hz AC, 60 HP Max
Speeds	Up to 200 fpm
Capacity	1200 to 5000 lbs.
	Cars in group can have
	different capacities
Travel	Up to 100'-0"



Ask your TK Elevator representative about our Advantage Packages, designed to make the H-Power modernization process as quick and convenient as possible for you and your tenants.

## **MOD Fusion fixtures:**



TK Elevator Corporation 788 Circle 75 Parkway SE Suite 500 Atlanta, GA 30339 P: +1 844 427 5461 www.tkelevator.com/us



© 2022 TK Elevator Corporation. | CA License #C11-651371 | 27056 | H-Power modernization brochure







